



**12,000 Mile
Service Checklist**

Customer _____

Date _____

Odometer _____

Exterior

Inspect:

- _____ Lights
- _____ Horn
- _____ Windshield wiper
- _____ Windshield washer
- _____ Mirrors
- _____ Body damage, missing hubcaps, etc
- _____ Chassis anti-rust treatment

- _____ Refill washer fluid
- _____ Lubricate door locks and hinges
- _____ Lubricate rear hatch hinges, check latch and alignment
- _____ Clean pollen filter

Test drive observations:

- _____ Rear hatch door ajar switch

Interior

Inspect:

- _____ Safety belts
- _____ Dome lights
- _____ Instrument panel warning lights
- _____ Center console warning lights
- _____ Climate controls
 - _____ Vent mode doors
 - _____ Blower speeds
 - _____ Heats to:
 - _____ Cools to:
- _____ Window operation
- _____ Mirror operation
- _____ Rear defog/mirror heat

Inspect for common Th!nk warranty items:

- _____ Mirror side covers
- _____ Loose mirror glass
- _____ A-pillar trim
- _____ Rear tires rubbing on fender liner
- _____ Headlight bulb sockets
- _____ Headlight ball and socket fittings
- _____ Tire inflation sticker
- _____ Key emblem
- _____ Fasten under-bumper to radiator

Shop temp and humidity:

- _____ Window up time:
- _____ Condenser fan operation

Powertrain and Driveline

Inspect:

- _____ Coolant level and condition
- _____ Radiator and hoses
- _____ Coolant pump operation
- _____ Transaxle fluid level and condition
- _____ CV joints and boots
- _____ EVSE charge port
- _____ Check diagnostic codes for all electronic control units

12V Electrical System

- _____ Conductance Test Results:

Steering

Inspect:

- _____ Power steering fluid level and condition
- _____ Intermediate steering shaft coupling
- _____ Steering rack boots, mounts

Suspension

Front

Inspect:

- | | |
|---|---|
| <input type="checkbox"/> Shocks | <input type="checkbox"/> Ball joints |
| <input type="checkbox"/> Springs | <input type="checkbox"/> Motor/gearbox mounts |
| <input type="checkbox"/> Sway bar bushings | <input type="checkbox"/> PCU mounts |
| <input type="checkbox"/> Control arm bushings | |
| <input type="checkbox"/> Tie rod ends | |
| <input type="checkbox"/> Wheel bearings | |

Rear

Inspect:

- Shocks
- Torsion bars
- Wheel bearings

Tires

Inspect:

- | | |
|--|-------------------------|
| <input type="checkbox"/> Tread depth: | |
| <input type="checkbox"/> Wear pattern: | |
| <input type="checkbox"/> Inflation | Inflation Specification |
| <input type="checkbox"/> LF | RF |
| <input type="checkbox"/> LR | RR |

Inflation Specification

Front: 36psi

Rear: 43psi

Rotate tires (if indicated)

Reset TPMS for rotated tires

Brakes

Inspect:

- Brake fluid level and condition
- Master cylinder
- Vacuum booster pump operation
- Brake lines and hoses
- Parking brake
- Front brakes**
 - Pad thickness
 - Rotor thickness
 - Minimum specification: 8mm (0.315 in)
- Rear brakes**
 - Shoe lining thickness
 - Drum diameter
 - Maximum specification, 204.4mm (8.047 in)
 - Wheel cylinder leakage

Clean and lubricate front pads (if required)

Clean and lubricate rear shoes

Additional comments:

- Lug bolts torqued to 110 Nm
- Spindle nuts torqued to 200 Nm and staked
-